

#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

• 1.1 Product identifier

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

Detailed descriptions:

® registered trademark of VACUUMSCHMELZE GmbH & Co. KG

• Information sheet - no.: IB17

• Remarks for information sheet

Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.

Articles are not subject to any legal obligation concerning production and distribution of material safety data sheets. The detailed information usually shown in a safety data sheet will be provided in the form of an 'Information sheet for articles' for specific alloys.

However, we expressly point out that these information sheets for articles are voluntarily produced data sheets which are not governed by the requirements of the REACH regulation.

- 1.2 Relevant identified uses of the substance or mixture and uses advised against Not applicable
- Application of the article: semi-finished products and parts
- 1.3 Details of the supplier of the information sheet
- Manufacturer/Supplier:

VACUUMSCHMELZE GmbH & Co.KG Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

- Further information obtainable from: Environmental Protection Department
- 1.4 Emergency telephone number:

Tel. no.: (\*\*49) 6181/38-0 Emergency tel. no.: via (\*\*49) 6181/38-0

### **SECTION 2: Hazards identification**

## • 2.2 Classification (substance or mixture)

Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

For articles there is no obligation to classify acc. to CLP -Regulation.

## • 2.2 Labelling according to Regulation (EC) No 1272/2008

Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

### Additional VAC information:

In the case of dust-producing processing, we recommend observance of the following warnings :

### • Hazard statements

Harmful if swallowed.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer by inhalation. Route of exposure: Inhalation.

May damage fertility.

Causes damage to organs through prolonged or repeated exposure.

May cause long lasting harmful effects to aquatic life.

# Precautionary statements

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Use personal protective equipment as required.

(Contd. on page 2)



### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 1)

In case of inadequate ventilation wear respiratory protection. Get medical advice/attention if you feel unwell.

### • Additional information:

Contains nickel, cobalt, beryllium. May produce an allergic reaction.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

### • 3.2 Chemical characterization:

• Description: Metal in compact form

## Components(composition):

The classifications given below reflect the classification of each <u>pure substance</u> respectively and are intended for information only

The legal classifications of the pure substances (harmonized classification according to substance list of the Annex VI of the CLP Regulation) got complemented, insofar as additional substance-specific information from accessible data sources (e.g. TRGS 905, toxicological studies) for health hazards and / or physical hazards are available.

CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9 RTECS: GF 8750000	cobalt  Resp. Sens. 1, H334; Carc. 1B, H350i; Repr. 1B, H360F; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 4, H413	~ 45%
CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7	nickel	~ 20%
CAS: 7440-47-3 EINECS: 231-157-5 RTECS: GB 4200000	chromium substance with a Community workplace exposure limit	~ 18%
CAS: 7440-33-7 EINECS: 231-143-9 RTECS: YO 7175000	tungsten substance with a Community workplace exposure limit	~ 4%
CAS: 7440-41-7 EINECS: 231-150-7 Index number: 004-001-00-7 RTECS: DS 1750000	beryllium  Acute Tox. 3, H301; Acute Tox. 2, H330; Carc. 1B, H350i; STOT RE 1, H372; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	< 0.3%

• NON-hazardous Ingredients		
CAS: 7439-89-6	iron (compact form)	rest%
EINECS: 231-096-4		
RTECS: NO 4565500		
CAS: 7439-98-7	molybdenum	~ 4%
EINECS: 231-107-2		
RTECS: QA 4680000		

#### Additional information:

For the wording of the listed hazard phrases refer to section 16.

### **Additional information for Cobalt:**

See also Chapter 11



#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 2)

#### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

#### After inhalation:

If metal vapours or dusts have been inhaled: Get the affected person out in the fresh air and call a doctor.

#### After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

# • After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Consult a doctor if the symptoms persist.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- Information for doctor: Beryllium, chronic lung diseases (berylliosis)
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Non-combustible.

Extinguishing agents must be adapted to the environment.

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic smoke / fumes (metal / metal oxides) is possible during heating or in case of fire. Do not inhale fumes.

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- 6.1 Personal precautions, protective equipment and emergency procedures No special measures required.
- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: No special measures required.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

## • 7.1 Precautions for safe handling

No safety precautions are necessary in the delivered form.

The appropriate industrial and environmental safety measures

must be taken for processing steps which cause dust (see also section 8):

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

(Contd. on page 4)



#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 3)

- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Not applicable
- Storage class: Not applicable
- 7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

### • Additional information about design of technical facilities:

Provide suction with filtering for good airing and ventilation of the work area during processing steps which cause dust. Air return is only permitted in exceptional cases.

If industrial vacuum cleaners are used, these must have dust class H (DIN EN 60335-2-69).

Suitable breathing apparatus must be used during repair and maintenance work to suction systems, especially when changing filters (see personal safety equipment).

#### • 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

For International Limit Values see Additional information below.

7440-48-4 cobalt			
ERB (Germany)	0.5 μg/m³ (A) bzw. 5μg/m³ (A)		
7440-02-0 nickel	7440-02-0 nickel		
` ,	Long-term value: 0.006A; 0.030E* mg/m³ 8(II);AGS, 24, Sh, Y, 10*, 31*		
7440-47-3 chromium			
\ /	Long-term value: 2 mg/m³ as Cr		
	Long-term value: 2 E mg/m³ 1(I);10, EU		
7440-33-7 tungsten			
MAK (Germany)	vgl.Abschn.IIb		
7440-41-7 beryllium			
	Long-term value: 0.00006* 0.00014** mg/m³ 1(I);AGS,X,10 *alveolengängig *einatembar; als Be		

## • DNELs

**DNELs for OSH purposes** 

In Germany, occupational exposure limits (AGW) of the Technical Rules on Hazardous Substances (TRGS) 900 continue to constitute workplace atmospheric limit values that are binding upon employers. Should no AGW and for example no maximum workplace concentration (MAK value) of the German Research Foundation (DFG) be available, the employer must also consider the DNEL during risk assessment.

(Source: Institut für Årbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA)) current values are available: http://www.dguv.de/ifa/gestis/gestis-dnel-liste/index.jsp.

_	2				
7440-48-4 cobalt					
	Inhalative	Long-term exposure - inhalation - local effects	0.04 mg/m³ (Ind)		
			0.0063 mg/m³ (Consumer)		
7440-02-0 nickel					
	Inhalative	Long-term exposure - inhalation - local effects	0.05 mg/m³ (Ind)		

(Contd. on page 5)



#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 4)

Long-term exposure - inhalation - systemic effects 0.05 mg/m³ (Ind)

#### Additional Occupational Exposure Limit Values for possible hazards during processing:

Compliance with the general dust limit value(s) (lung penetrating and/or inhalable fraction) must be ensured. If the occurrence of chrome (VI) compounds cannot be ruled out, the TRGS 910 (acceptance and tolerance concentrations)

must be considered!

The AGW for nickel is to be used only for nickel metal.

For thermal processes in the presence of atmospheric oxygen, oxidic nickel compounds must always be assumed and the ERB (TRGS 910) must be applied.

#### Additional information:

- The lists valid during the making were used as basis.
- GESTIS International Limit Values:

http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Internationale-Grenzwerte-für-chemische-Substanzen-limit-values-for-chemical-agents/index.jsp

#### • 8.2 Exposure controls

#### Personal protective equipment:

# • General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

### Respiratory protection:



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3, for example:

- Full face mask (EN 136)
- Breathing mask (EN 149) FFP2 or FFP3
- 10 times the limit value (FFP2)
- 30 times the limit value (FFP3)

Recommendation: P3

#### Protection of hands:



Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

# Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

- Penetration time of glove material -
- Eye protection:



In the event of larger quantities of dust:

Wear protective glasses / EN 166, poss. with side protection.

### • Limitation and supervision of exposure into the environment

The legal issue values and limitations are to be paid attention!

\_ =



#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 5)

# **SECTION 9: Physical and chemical properties**

• 9.1 Information on basic physical and chemical properties

General Information

• Appearance:

Form: Semi-finished products/parts: e.g. strip, wire, parts and bars

Colour: MetallicOdourlesspH-value: Not applicable.

Change in condition

Melting point/Melting range (approx.): 1,400-1,500 °C

Auto-ignition temperature: Not applicable
Explosive properties: Not applicable
Vapour pressure: Not determined.
Density (approx.) at 20 °C: 8.5 g/cm³
Not determined.

• Solubility in / Miscibility with

water: Insoluble.

• 9.2 Other information No further relevant information available.

# **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions

Hydrogen is released in contact with acid which can cause explosive gas mixtures.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity

Harmful if swallowed.

• LD/LC50 v	• LD/LC50 values:		
7440-48-4	7440-48-4 cobalt		
Oral	LD50	550 mg/kg (rat)	
Inhalative	LC50/4 h		
		siehe zusätzlicher toxikologischer Hinweis / see additional toxicological information	
7440-02-0	7440-02-0 nickel		
Oral	LD50	>9,000 mg/kg (rat)	
7440-41-7	7440-41-7 beryllium		
Inhalative	LC50/4 h	≤0.25 mg/l (rat)	
		für Aerosole oder Stäube	
		(Contd. on page 7)	

(Contd. on page 7)



#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

# Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 6)

## Primary irritant effect:

Skin corrosion/irritation see sensitization

#### Serious eye damage/irritation

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

#### Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

### Additional toxicological information:

Subsequent users should be aware of the fact that Co-metal fine powder are classified as "acute toxic if inhaled, Category 1" (no legal classification); LC50 4hr ≤0,05 mg/l.

In case the subsequent use of product generates fine Co-metal particles (e.g. dust), protection measures such as described in Chapter 7 and 8 of this information sheet must be applied.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

May cause cancer by inhalation. Route of exposure: Inhalation.

- Reproductive toxicity
- May damage fertility.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure
- Causes damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- •12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Alloys in solid form do not pose an ecological threat.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation Observe offical regulations.
- Uncleaned packaging: Not applicable

# SECTION 14: Transport information

- Transport/Additional information:
- Land transport ADR/RID (cross-border):
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

(Contd. on page 8)



#### for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 7)

- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air Transport ICAO-TI and IATA-DGR:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 27
- National regulations:
- Other regulations, limitations and prohibitive regulations

e.a

- 1272/2008/EG (CLP)
- 1907/2006/EG (REACH)
- German Hazardous Substances
- 15.2 Chemical safety assessment: Void (for articles)

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H350i May cause cancer by inhalation. Route of exposure: Inhalation.
- H351 Suspected of causing cancer. Route of exposure: Inhalation.
- H360F May damage fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H413 May cause long lasting harmful effects to aquatic life.

## Department issuing SDS:

Department OPS-C SE

Tel. 06181/38-2045

#### • Contact:

**Environmental Protection Department** 

Tel. 06181/38-2359

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)



# for articles

Printing date 09.01.2019 Version number 3 Revision: 09.01.2019

# Trade name: NIVAFLEX® 45/5, NIVAFLEX® Plus

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
BRT: Persistent Resecumination and Toxic

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic PBT: Persistent, Bioaccumulative and Toxic

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

#### Sources

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe